

320 FOOT VALVE EXTRACTOR

The 320 foot valve extractor is designed for use with the 150 and 151 1½" foot valves. This 20 lb. extractor valve provides a means to remove foot valves easily from underground storage tanks for cleaning or servicing. The 320 foot valve extractor is gasket sealed to prevent loss of prime caused by air being sucked in through the top fitting.

E

Model		Size	А		В	
IVIOQEI	In	mm		mm		mm
32030201	$4.00 \times 4.00 \times 1.50$	102.00 × 102.00 × 38.00	5.50	139.70	7.25	184.15
32030202	$4.00\times4.00\times2.00$	102.00 × 102.00 × 51.00	5.50	139.70	7.25	184.15



THREAD SIZE

Model		⁼ emale read		t Male hread	Outlet Thread		Top Thread	
	In	mm	In		In	mm		mm
32030201	1.50	38.00	4.00	102.00	1.50	38.00	4.00	102.00
32030202	1.50	38.00	4.00	102.00	2.00	51.00	4.00	102.00

REPLACEMENT PARTS			
Model	Description		
32010201	Suction stub adapter		
32010301	Cap assembly		
32110001	Extractor wrench		
32010401	Kit - cap with gasket		

MATERIALS

- Body: zinc-plated cast iron.
- Cap: bronze.
- Suction stub adapter: bronze.
- Gasket: leather.