

# WHY GPI?

## GPI OFFERS MORE FEATURES THAN OTHER PRODUCT LINES.

straight or weight-centering base. These pumps fit high-flow applications requiring either a 12- or 24-volt DC pump. Contact GPI Customer Service for information on the best pump for your unique application.

**GPI**

**PUMP  
SPECS**



MODEL	M-3425-ML or -AL	M-3425CS-PO
PART NUMBER	133260-01 w/manual nozzle 133260-02 w/auto nozzle	133262-04 (Pump only model)
VOLTAGE & TYPE	24-Volt DC - Vane	24-Volt DC - Vane
FLOWRATE	Up to 25 GPM (95 LPM)	Up to 25 GPM (95 LPM)
DUTY CYCLE	30 min. On / 30 min. Off	30 min. On / 30 min. Off
POWER CORD	15 ft. (4.6m) of 10/3 AWG	15 ft. (4.6m) of 10/3 AWG
NOZZLE	Choice of manual or automatic shutoff.	None
SUCTION PIPE	None	None
HOSE	12 ft. (3.7m) x 1 in.	None
MOTOR PROTECTION	20 amp circuit breaker	20 amp circuit breaker
UNIQUE FEATURE	Highest flow, 24-volt pump, reduces time spent refueling.	Weight centering inlet base - includes check valve.
USE WITH	Gasoline (alcohol blends E15), diesel fuel (biodiesel blends B20) and kerosene.	Gasoline (alcohol blends E15), diesel fuel (biodiesel blends B20) and kerosene.
APPROVALS	Motor is U.L. Listed to U.S. and Canadian Standards	Motor is U.L. Listed to U.S. and Canadian Standards
WARRANTY	2 Year	2 Year