

HARDWALL HOSE ASSEMBLY

FLEX-ING™ brand Hardwall Hose features an abuse-resistant, solid wire braid construction that prevents kinking and assures a long service life and minimal maintenance. The ozone-resistant outer hose construction prevents ozone cracking and wear. This high quality hose offering features robust hose and fitting designs built to stand up to the harshest forecourt conditions.



HIGHLIGHTS

- Available in 5/8", 3/4" and 1" diameters, a variety of curb and whip hose lengths, and fixed or swivel fitting options.
- Available with swivel fitting option for enhanced ease of use.
- Resistant to ozone cracking and wear.
- High gloss cover retains color quality.
- Stainless steel ferrules and fluoroelastomer seals to ensure compatibility with gasoline, diesel, Ethanol blends (up to E10) and biodiesel blends (up to B5).
- Compatible with reel or retractable cable dispensing applications.

SPECIFICATIONS

- Tube: Synthetic rubber
- Cover: Ozone-resistant rubber
- Fittings: Machined nickel-plated carbon steel with chrome finish
- Reinforcement: Hardwall wire braided
- Temperature rating: -40 °F to 140 °F (-40 °C to 60 °C)
- For use with gasoline, diesel, Ethanol blends (up to E10) and biodiesel blends (up to B5).

Approvals/Certifications

- UL and cUL listed (UL 330, CAN/ULC-S612).

ORDERING INFORMATION

Complete model numbers have a specific order and are created using the following guidelines:

FLHFR A B C D E

FLHFR = FLEX-ON™ Hardwall Hose

A = Hose Diameter

1 = 5/8" 3 = 1"
2 = 3/4"

B = Hose Length Feet

Use three-digit format

C = Hose Length Inches

Use two-digit format

D = Hose Color Options

Blank = Black GR = Green
YL = Yellow BL = Blue
RD = Red

E = Swivel Options

Blank = No Swivels
SWOE = Swivel on one end
SWEE = Swivel on both ends

Example: FLHFR200806YLSWOE = FLEX-ON™ Hardwall Hose, 3/4" diameter, 8 feet, 6 inches length, yellow color, swivel on one end.



franklinfueling.com
3760 Marsh Rd. • Madison, WI 53718, USA
Tel: +1 608 838 8786 • Fax: +1 608 838 6433
Tel: USA & Canada +1 800 225 9787 • Tel: UK +44 (0) 1473 243300
Tel: Mex 001 800 738 7610 • Tel: FR +33 (0) 1 69 21 41 41 • Tel: CH +86 10 8565 4566



© 2017 Franklin Fueling Systems. All Rights Reserved.

FFS-0273 12-17